



Amended
PLAT
OF THE
TOWNSITE OF
DAYTON

Embracing lots 7 & 8 in Sec. 3.
T. 24 N. R. 21 W.
Principal Meridian
MONTANA
Scale ft. to an inch.

Department of the Interior,
General Land Office,
Washington, D.C., March 3, 1909.

I hereby certify that the above plat of the Townsite of Dayton, embracing Lots 7 and 8 in Sec. 3, T. 24 N., R. 21 W., P.M., Montana, amended to conform to the provisions of Section 17 of the act of June 2, 1906, (34 Stat. 354) is strictly conformable to the field notes of the survey thereof, executed by Chas. M. Poffen, Examiner of Surveys August 5 to August 14, 1907, under instructions dated July 3, 1907, on file in this office which have been examined and approved.

[Signature]
Commissioner

Department of the Interior,
Washington, D.C., June 1, 1909.
Approved under provisions of the act of June 21, 1906.

[Signature]
First Assistant Secretary

12-16-09 4771647 3-2-10
FROM: LANCE (D) 407 3-7-10
DHL: WINDFILL 407 3-7-10
TELETYPE

LEGEND

All regular blocks 300 x 300 ft. Fractional blocks dimensioned as indicated;
All lots 50 x 140 ft. except in block 16, 50 x 200; block 19, 30 x 130.4 ft. and in fractional blocks dimensioned in detail as indicated; blocks 1 to 8 and 10 to 15, inclusive, and blocks 17 and 18, divided by Alleys 20 ft. wide; block 9 and fractional block 22 are reserved for public purposes; A Street, 29.2 ft. wide at east end and 54.3 ft. wide at west end, and B, C & D Streets, 80 ft. wide run E and W, 1 st. 2nd, 3rd, 4th, 5th and 6th Streets 80 ft. wide and 7th Street 45.5 ft. wide at North end and 50.6 ft. wide at South end, run N & S; Lake and Front Streets 80 ft. wide follow the meander-line of Flathead Lake as indicated. Permanent monuments consisting of iron bolts 7/8 in. diam., 20 ins. long are set 6 ins. below surface at intersection of center lines of 3rd, 6th and B Streets.

11.5 FT. TIE LINE 490
The above survey was made June 14, 1900
by Chas. M. Poffen, Surveyor
and is on file in this office
under file No. 4771647